

P2C Peripheral Products



WATCHING THE
P2C SERIES
www.imupos.com



MSR



Card Reader Interface type
RJ11 (RS232 Level, Power Pin 1 +5V)



MSR
Supplied 1,2,3 Track



Interface
RS-232



Sound
Buzzer



Operating Temperature
0 °C to +50 °C



Power Input
DC 5V



Card Reader Interface type
RJ50 (RS232 Level, Power Pin 1 +5V)



Display Type
FSTN LCD



Brightness
500 cd/m²



Display Color
Navy Blue



Interface
RS-232



Number of Characters
20 columns x 2 lines



Character Size
8x16 Dot Matrix



Operating Temperature
0 °C to +50 °C



Input Voltage
DC 5V

Customer Display



**Card Reader Interface type**

DB9(RS232 Level, Power Pin 9 +5V)

**Data Protocol**

1-Wire®

**Interface**

RS-232

**Operating Temperature**

0 °C to +50 °C

**Power Input**

DC 5V

Dallas Reader



RFID Reader

**Card Reader Interface type**

DB9(RS232 Level, Power Pin 9 +5V)

**Transmit Frequency**

125 kHz standard

**Transponder**H4001 / H4002 / EM4100 / 4102
EM Card Read only**Reading Distance**

Up to 5 cm with EM card

**Interface**

RS232

**Operating Temperature**

0 °C to +50 °C

**Power Input**

DC 5V

Hardware
Brand**P2C**Software
Brand**UP SOLUTION**